



△△ SPECIFICATION
 Current Rating:3 Amp
 Voltage Rating:250V AC/RMS 60Hz
 Contact Resistance:20 Milliohms Max. At 1 Amp DC
 Insulation Resistance:1000 Megaohms At 500V DC
 Withstand Voltage:1000V AC/RMS 60Hz
 For 1 Minute
 △ Operation Temperature:-55°C~+105°C
 Insulator:PBT+G.F.(UL94V-0),Black
 Contact:Brass,Gold Plated On Contact Area,Tin
 Plated On Solder Tails,Over Nickel
 Shell:Steel,Tin Plated Over Copper
 Clinch Nut:Brass,Nickel Plated
 Boardlock:Brass,Tin Plated
 Screw:Brass,Nickel Plated
 RoHS Compliant

△ DDM XX S Z J - H
 (1) (2) (3) (4) (5) (6)
 (1) DDM:D-SUB DIP Straight Metal Shell With Plastic
 (2) XX:No. Of Position
 (3) S:Female
 (4) Z:Rivet With Boardlock
 (5) J:With Front Jackscrew
 (6) H:RoHS Compliant

△ Pin	A	B	D	E
09	30.81	24.99	16.33	11.08
15	39.20	33.30	24.70	19.39
25	53.05	47.04	38.40	33.24
37	69.40	63.50	54.80	49.86

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.38 X.* ±3* .XX ±0.25 X.* ±1.0* .XXX ±0.13
PART No. DDMXXSZJ-H		MEI		
DRAWING No. DDMXXSZJ-H		HZF		
SCALE NONE		SONG		
REV.	B3	UNIT mm		

NO.	REV.	REVISIONS	CHK	DATE
△ B3		Modify Data	HZF	07/04/2012
△ B2		Add Operation Temp.	HZF	09/08/2011
△ B1		Modify Data	HZF	07/15/2011
△ B0		NEW RELEASE	BECKY	06/06/2006