



SPECIFICATION
 Current:1.5A Max.
 Voltage:30V Max.
 Withstand Voltage:500V AC
 Contact Resistance:30 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min.
 Temperature Range:-55°C~+85°C
 Mating Force:35N Max.
 Withdrawal Force:10N Min.
 Durability:1500 Cycles Min.
 Housing:PBT+30%G.F.(UL94V-0)
 Contact:Brass,Gold Flash On Contact Area,Bright Tin Plated On SolderTails,Over Nickel
 Shell:Brass,Nickel Plated Over All
 Back Cover:PBT+30%G.F.(UL94V-0),White
 RoHS Compliant

USB 2X02 SS - XX - H
 (1) (2) (3) (4) (5)

- (1) USB:USB Series
- (2) 2X02:B Type 4 Pins
- (3) SS:Female Solder Wire Molding Type
- (4) XX:Housing Color
 Blank:White
 BK:Black
- (5) H:RoHS Compliant

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.38 .X* ±2* .XX ±0.25 .XX* ±1* .XXX ±0.13 .XXX* ±0.5*
PART No. USB2X02SS-XX-H		EMILY		
DRAWING No. USB2X02SS-XX-H		CHECKED BY HZF		
SCALE		DRAWING BY SONG		
SCALE	NONE	REV.	A1	UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△A1		Modify Data	HZF	11/16/2013
△A0		NEW RELEASE	HZF	03/05/2011