



**△ SPECIFICATION**  
 Housing:PA66+G.F.(UL94V-0)  
 Contact&Shorting Buss:Phosphor Bronze  $\phi$ 0.45mm  
 Cavity Confirms To FCC Rules And Regulations  
 Part 68,Subpart F.  
 RoHS Compliant

**△△ MJ G 0808 X X XX - XX - H**  
 (1) (2) (3) (4) (5) (6) (7) (8)

(1) MJ:Modular Jack  
 (2) G:Great Type  
 (3) 0808:8P8C  
 (4) X:Insulator Color  
 G:Gray  
 K:Black  
 (5) X:Without Panel Stop  
 (6) XX:Contact Finish  
 01:Gold Flash Over All,Over Nickel  
 06:Gold Plated 6u" Over All,Over Nickel  
 15:Gold Plated 15u" Over All,Over Nickel  
 30:Gold Plated 30u" Over All,Over Nickel  
 (7) XX:Loop Option  
 Blank:Without Shorting Buss  
 SB:With Shorting Buss Pin #1/4,5/8  
 (8) H:RoHS Compliant

**AUK** A MEMBER OF AUK GROUP  
**太聯事業股份有限公司**  
**AUK CONTRACTORS CO., LTD.**

CATEGORY		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X $\pm$ 0.25 .XX $\pm$ 0.13 .XXX $\pm$ 0.05 ANG. $\pm$ 0.5°
PART No. <b>△△</b> MJG0808XXX-XX-H		EMILY		
DRAWING No. <b>△△</b> MJG0808XXX-XX-H		CHECKED BY HZF		
SCALE NONE		DRAWING BY SONG		
REV.	B2	UNIT	mm	

NO.	REV.	REVISIONS	CHK	DATE
△	B2	Modify P/N: MJG0808GXXX-H --> MJG0808XXX-XX-H	HZF	06/25/2013
△	B1	Modify P/N: MJG0808GX06-H --> MJG0808GXXX-H	HZF	06/06/2013
△	B0	NEW RELEASE	HZF	05/15/2008