



△ SPECIFICATION

Housing:PA9T(UL94V-0),Black
 Insert Housing:PA46(UL94V-0),Black
 Heat Deflection Temperature:290°C
 Contact:Phosphor Bronze
 Cavity Confirms To FCC Rules And
 Regulations Part 68,Subpart F.
 RoHS Compliant

△ MJ U W 0808 K X XX P - H
 (1) (2) (3) (4) (5) (6) (7) (8) (9)

- (1) MJ:Modular Jack
- (2) U:Height=13.14mm
- (3) W:SMT Right Angle
- (4) 0808:8P8C
- (5) K:Insulator Color Black
- (6) X:Without Panel Stop
- (7) XX:Contact Finish
 06:Gold Plated 6u" On Contact Area,Gold
 Flash On Other Area,Under Nickel
 15:Gold Plated 15u" On Contact Area,Gold
 Flash On Other Area,Under Nickel
 30:Gold Plated 30u" On Contact Area,Gold
 Flash On Other Area,Under Nickel
 50:Gold Plated 50u" On Contact Area,Gold
 Flash On Other Area,Under Nickel
- (8) P:With Two Post
- (9) H:RoHS Compliant

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY		APPROVED BY	
PART No. △ MJUW0808KXXXP-H		MEI	
DRAWING No. MJUW0808KXXXP-H		CHECKED BY HZF	
SCALE NONE		DRAWING BY WZL	
REV. A1		UNIT mm	

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
 △ .X ±0.25
 .XX ±0.20
 .XXX ±0.10

NO.	REV.	REVISIONS	CHK	DATE
△ A1		Modify P/N: MJUW0808KX06P--> MJUW0808KXXXP-H, Add 15u"	HZF	04/16/2011
△ A0		NEW RELEASE	HZF	08/20/2007