




One 204-pin SODIMM Up to 8GB DDR3 1333/ 1600 SDRAM



Intel® Core™ i7/ i5/ i3/ Celeron® (Socket-G2) Socket

## Features

- Intel® Core™ i7/ i5/ i3 (Socket-G2) Processors
- Intel® QM77 Chipset
- One 204-pin SODIMM Up to 8GB DDR3 1333/ 1600 SDRAM
- Support CRT, LVDS, Display Port, HDMI, DVI
- Intel® High Definition Audio
- Intel® 82579LM Gigabit Ethernet
- 7 PCIe1, 1 PCIe16, 4 SATA, 8 USB 2.0, 4 USB 3.0, 8-bit GPIO
- +9 ~ +19V Wide Range Power Input
- Type 6 Pin-out
- Support TPM

## Specifications

### System

• CPU	Intel® Core™ i7/ i5/ i3/ Celeron® (Socket-G2) Processors
• BIOS	AMI 64Mbit SPI BIOS
• System Chipset	Intel® QM77
• System Memory	One 204-pin SODIMM Up to 8GB DDR3 1333/ 1600 SDRAM
• Expansion	7 PCIe1, 1 PCIe16
• EEPROM	ATMEL AT24C02 (Optional)

### I/O

• MIO	4 x Serial ATA, SMBus/ I <sup>2</sup> C Bus
• USB	8 x USB 2.0, 4 x USB 3.0
• DIO	4-bit GPI and 4-bit GPO

### Display

• Chipset	Intel® QM77 Chipset Integrated
• Memory	DVMT 5.0 Up to 512MB
• Resolution	CRT Mode: 2048 x 1536 LCD/ Simultaneous Mode: 1920 x 1200
• LVDS Interface	Dual-Channel 18/24-bit LVDS
• Display Supported	HDMI, DVI, Display Port

### Audio Interface

• Chipset	Intel® QM77 Integrated
• Interface	Intel® High Definition Audio

### Ethernet

• LAN	Intel® 82579LM (PHY) Gigabit Ethernet
• Ethernet Interface	10/ 100/ 1000 Base-Tx Gigabit Ethernet Compatible

### Mechanical & Environmental

• Power Requirement	+9 ~ +19V
• ACPI	Single Power ATX Support S0, S3, S4, S5 ACPI 3.0 Compliant
• Power Type	AT/ ATX
• Operating Temperature	0 ~ 60°C (32 ~ 140°F)
• Storage Temperature	-40 ~ 75°C (-40 ~ 167°F)
• Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
• Size (L x W)	5" x 3.7" (125mm x 95mm)
• Weight	0.44lbs (0.2kg)

- 1 Embedded System
- 2 Qseven Module
- 3 ETX/XTX COM Express
- 4 3.5" SBC
- 5 EPIC
- 6 5.25" SBC
- 7 ATX
- 8 Micro ATX
- 9 Mini ITX
- 10 Nano ITX
- 11 ACP
- 12 Rack Mount System
- 13 Mini ITX System
- 14 Peripherals
- 15 Index

## Ordering Information

- **ESM-QM77**  
Intel® Core™ i7/ i5/ i3 COM Express Type 6 Module with Intel® QM77 Chipset
- **EEV-EX14**  
COM Express Type 6 Carrier Board for Evaluation