



REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	LJH 04/27/05'	~	LJC 04/27/05'
B	ADD DIM TYPE	YCH 07/04/07'	~	LJC 07/04/07'
C	ADD P/N CODE	LJC 12/09/13'		



NOTES:

1. MATERIAL&FINISHES

- 1.1 INSULATOR:THERMOPLASTIC(UL 94V-0).
- 1.2 CONTACT MATERIAL: COPPER ALLOY.

2. SPECIFICATION

- 2.1 CURRENT RATING:1.5 Amp.
- 2.2 INSULATION RESISTANCE:1000MΩ Min.
- 2.3 DIELECTRIC WITHSTANDING:600VAC.
- 2.4 CONTACT RESISTANCE:20mΩ Max.
- 2.5 OPERATING TEMPERATURE:-40°C TO +105°C.

3. PRODUCT NUMBER CODE:

DS1025-01 - X X X X X X - X

- PLATING LEVEL(FOR GOLD ONLY)©  
3A: 0.8-1.2u" AA: LEVEL AA  
A: LEVEL A B: LEVEL B
- DIM.A B TYPE  
1: TYPE 1  
2: TYPE 2  
3: TYPE 3  
4: TYPE 4  
5: TYPE 5  
.....
- MOUNTING TYPE  
V: VERTICAL TYPE
- HOUSING COLOR  
B: BLACK
- CONTACT PLATING  
8: FULL GOLD FLASH  
6: TIN
- CONNECTOR TYPE  
P: PLUG
- No.OF CONTACTS  
1\*2~1\*40

N:NUMBER OF CONTACTS

Tel:86-574-63508787

Fax:86-574-63510817

E-mail:sales@connfly.com


http://www.connfly.com

Add:East Industry Zone KuangYan

Town:Xianningbo China

P.C:315333


RECOMMENDED PCB LAYOUT  
(TOLERANCE=±0.05)



TYPE	DIM A	DIM B
1	4.00	2.80
2	6.00	3.00
3	2.80	10.20
4	2.80	15.20
5	7.00	3.00
6	10.20	2.80
7	3.70	3.00
8		

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°
DRAWING TYPE		CUSTOMER	
SCALE	1:1	SHEET	1 OF 1
DRAWING NO.	C-DS1025-01-XXXXXX-X-C		

PROJECTION	TITLE	2.0mm PIN HEADER SINGLE ROW STRAIGHT TYPE	
UNITS	mm	SHEET SIZE	A4
SHEET SIZE	A4	SERIES	DS1025-01 SERIES


**晨翔电子有限公司**  
**CONNFLY® CONNFLY ELECTRONIC CO., LTD**