


REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	LL 09/25/06'		



NOTES:

1. SPECIFICATION:

- 1.1 CONTACT RESISTANCE: 30mΩ MAX.
- 1.2 DIELECTRIC WITHSTANDING VOLTAGE: 250V AC(rms) FOR 1 MINUTE.
- 1.3 INSULATION RESISTANCE: 500MΩ MINI.
- 1.4 OPERATING TEMPERATURE: -20°C~+80°C.

2. PRODUCT NUMBER CODE:

DS1028 - X X X X X

PROFILE HEIGHT(DIM A):
1: 3.50mm
2: 5.00mm

CONTACT PLATING:
F1: FULL GOLD FLASH
N: NICKEL
2: GOLD+NICKEL

HOUSING COLOR:
B: BLACK U:BLUE Y:YELLOW
W: WHITE E:GREEN R:RED

HOUSING TYPE:
A:OPEN B:CLOSE

No.OF CONTACTS:
2: 2pin

SERIES No:
DS1028

Tel:86-574-63510817
Fax:86-574-63510817
E-mail:sale@zhenqin.com.cn
Http://www.connfly.com

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°

PROJECTION	TITLE
	MINI JUMPER PITCH 2.00mm
UNITS	mm
SHEET SIZE	A4
SERIES	DS1028 SERIES

2	HOUSING		PBT	SEE NOTES	DRAWING TYPE	CUSTOMER	
1	CONTACT		COPPER ALLOY	SEE NOTES	SCALE	1:1	SHEET 1 OF 1
ITEM	PART NAME	PART NO.	MATERILAS	FINISHED	DRAWING NO.	C-DS1028-XXXXX	

晨翔电子有限公司
CONNFLY CONNFLY ELECTRONIC CO. LTD