



SPECIFICATION

Current Rating:2.5A AC/DC
 Voltage Rating:250V AC/DC
 Withstand Voltage:800V AC/Minute
 Contact Resistance:10 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min.
 Temperature Range:-25°C~+85°C
 Insulator:PA66(UL94V-0)
 RoHS Compliant

PHD XX H - H
 (1) (2) (3) (4)

- (1) PHD:2.0mm PHD Board To Wire
- (2) XX:No. Of Position
- (3) H:Female Housing
- (4) H:RoHS Compliant

Pin	A	B	C
04	2.00	5.90	4.40
06	4.00	7.90	6.40
08	6.00	9.90	8.40
10	8.00	11.90	10.40
12	10.00	13.90	12.40
14	12.00	15.90	14.40
16	14.00	17.90	16.40
18	16.00	19.90	18.40
20	18.00	21.90	20.40
22	20.00	23.90	22.40
24	22.00	25.90	24.40
26	24.00	27.90	26.40
28	26.00	29.90	28.40
30	28.00	31.90	30.40
32	30.00	33.90	32.40
34	32.00	35.90	34.40
36	34.00	37.90	36.40
38	36.00	39.90	38.40
40	38.00	41.90	40.40

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY		APPROVED BY EMILY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.38 .XX ±0.25 ANG.
PART No. PHDXXH-H		CHECKED BY HZF		
DRAWING No. PHDXXH-H		DRAWING BY GAO		
SCALE	NONE	REV.	A0	
		UNIT mm		NO. REV.

△ A0	NEW RELEASE	HZF	10/12/2012
NO. REV.	REVISIONS	CHK	DATE