



SPECIFICATION

Current Rating:3A AC/DC
 Voltage Rating:250V AC/DC
 Contact Resistance:20 Milliohms Max.
 Withstanding Voltage:1500V AC/Minute
 Insulation Resistance:1000 Megaohms Min.
 Operation Temperature:-25°C~+85°C
 Insulator:PA66+15%G.F.(UL94V-0)
 Pin:Brass,Gold Flash Over All,Over Nickel
 RoHS Compliant

MCG XX R G - H
 (1) (2) (3) (4) (5)

- (1) MCG:2.54 MCG Series
- (2) XX:No. Of Position
- (3) R:Male DIP Right Angle
- (4) G:Gold Flash Over All,Over Nickel
- (5) H:RoHS Compliant

Pin	A	B
02	2.54	7.62
03	5.08	10.16
04	7.62	12.70
05	10.16	15.24
06	12.70	17.78
07	15.24	20.32
08	17.78	22.86
09	20.32	25.40
10	22.86	27.94
11	25.40	30.48
12	27.94	33.02
13	30.48	35.56
14	33.02	38.10
15	35.56	40.64
16	38.10	43.18
17	40.64	45.72
18	43.18	48.26
19	45.72	50.80
20	48.26	53.34

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.30 .X ±0.25 .XX ±0.20 .XXX ±0.015
PART No. MCGXXRG-H		EMILY		
DRAWING No. MCGXXRG-H		CHECKED BY HZF		
SCALE NONE		DRAWING BY SONG		
REV.	A1	UNIT mm	NO. REV. REVISIONS	

NO. REV.	A1	Modify Data	HZF	10/22/2013
NO. REV.	A0	NEW RELEASE	HZF	10/03/2012
NO. REV.	REVISIONS		CHK	DATE