



NOTES:

1. Rating: 300V 15A
PITCH: 5.00 mm
2. Insulation Withstands Voltage:
AC 2000V at 1 minute
3. Insulation Resistance:
500MΩ or more at DC500V
4. Using Temperature Range:
-40°C~+105°C
5. RoHS compliance

Normal Geometric Tolerancing

0 to 100	0.2	0 to 10	0.2
over 100 to 150	0.3	over 10	0.3
over 150	0.5		

Total Pitch Tolerances

0D≤30	±0.20	0~30	±0.25
30D≤53	±0.25	over 30~53	±0.30
53D≤70	±0.30	over 53~70	±0.35
70D≤90	±0.35	over 70~90	±0.44
90D≤115	±0.44	over 90~115	±0.55
115D≤150	±0.55	over 115~150	±0.70
150D≤200	±0.70	over 150~200	±0.85
200D≤250	±0.85	over 200~250	±1.00
250D≤320	±1.00	over 250~320	±1.20

REV.	CONTENT	CHK.	DATE

DWG.	WXY	DATE	10.03.24	UNITS	MM	SHEET/OF	1 / 1
CHK.		DATE		SCALE	5:1		
APP.		DATE		NAME	0135-19XX		

2	SOLDER PIN	COPPER-ALLOY	Tin Plated
1	HOUSING	PA66	UL94-V0 GRAY
ITEM	NAME OF PART	MATERIAL	NOTES

DINKLE ENTERPRISE CO., LTD

DINKLE

DWG NO. SP-03-013519XX