



NOTES:

1. Rating: 300V 15A
PITCH: 5.00 mm
2. Insulation Withstands Voltage:
AC 2000V/MIN
3. Insulation Resistance:
500MΩ or more at DC500V
4. Using Temperature Range:
-40°C~+105°C
6. Suitable Electric Wire: AWG 14~26
7. Assemble 2P, only need one 0134-1001
and one 0134-1002, and one 0134C1XX00
8. Assemble more than 2P, only need
(p-2) 0134-1001 and two 0134-1002,
and one 0134C1XX00
9. RoHS Compliance

Normal Geometric Tolerancing				
—	//	≡	⊥	
0 to 100	0.2	0.3	0 to 10	0.2
over 100 to 150	0.3		over 10	0.3
over 150	0.5			
Total Pitch Tolerances		Normal dimension Tolerances		
0<U<=30	±0.20	0~30	±0.25	
30<U<=53	±0.25	over 30~53	±0.30	
53<U<=70	±0.30	over 53~70	±0.35	
70<U<=90	±0.35	over 70~90	±0.44	
90<U<=115	±0.44	over 90~115	±0.55	
115<U<=150	±0.55	over 115~150	±0.70	
150<U<=200	±0.70	over 150~200	±0.85	
200<U<=250	±0.85	over 200~250	±1.00	
250<U<=320	±1.00	over 250~320	±1.20	

3	COVER	PA66	UL94-V0 GREEN
2	0134-1002	PA66	UL94-V0 GREY
1	0134-1001	PA66	UL94-V0 GREY
ITEM	NAME OF PART	MATERIAL	NOTES

DWG.	ZYJ	DATE	12.11.16	UNITS	MM	SHEET/OF	1 / 1
CHK.		DATE		SCALE	3:1 (:)		
APP.		DATE		NAME		0134-11XX	
				DINKLE ENTERPRISE CO., LTD		DWG NO.	SP-03-013411XX

REV.	CONTENT	CHK.	DATE
△ 2			