



NOTES:

1. Insulation Withstands Voltage:
AC 2500V at 1 minute
2. Insulation Resistance:
500MΩ or more at DC500V
3. Using Temperature Range:
-40°C~+105°C
4. Screw Torque Value: 0.6N.m
5. Suitable Electric Wire: AWG 28~10
(IEC 0.14~4mm²)
6. RoHS compliance
7. CLAMP与CONDUCTOR需铆接

Normal Geometric Tolerancing					
—	//	≡	⊥		
0 to 100	0.2		0 to 10	0.2	
over 100 to 150	0.3	0.3	over 10	0.3	
over 150	0.5				

Normal dimension Tolerances	
0~30	±0.25
over 30~53	±0.30
over 53~70	±0.35
over 70~90	±0.44
over 90~115	±0.55
over 115~150	±0.70

5	CLAMP	STELL	Zn Plated
4	WIRE CAGE	STELL	Zn Plated
3	CONDUCTOR	COPPER-ALLOY	Tin Plated
2	SCREW	STEELL	Zn Plated
1	HOUSING	PA66	UL94-V0 YELLOW-GREEN
ITEM	NAME OF PART	MATERIAL	NOTES

DWG.	W.ZJ	DATE	12.06.18	UNITS	MM	SHEET/OF	1/1
CHK.		DATE		SCALE	2:1 (:)		
APP.		DATE		NAME		DK4N-PE	
				DINKLE ENTERPRISE CO.,LTD		DWG NO. SP-03-DK4NPE00	

REV.	CONTENT	CHK.	DATE
1			