



NOTES:

1. Rating: 600V 15A
2. Insulation Withstands Voltage: AC 2500 V/MIN
3. Insulation Resistance: 500MΩ or more at DC500V
4. Using Temperature Range: -40°C~+125°C
5. Screw Torque Value: 0.5 N.m
6. Suitable Electric Wire: AWG 14~22
7. RoHS compliance

Normal Geometric Tolerancing					
	-	//	≡	⊥	
0 to 100	0.2			0 to 10	0.2
over 100 to 150	0.3		0.5	over 10	0.3
over 150	0.5				
Normal dimension Tolerances					
0~30	±0.25				
over 30~53	±0.30				
over 53~70	±0.35				
over 70~90	±0.44				
over 90~115	±0.55				
over 115~150	±0.70				
over 150~200	±0.80				
over 200~250	±0.90				

2	DKBC10-XXP	PC	UL 94V2 LIMPID
1	DKB10-XXP	PC	UL 94V2 BLACK
ITEM	NAME OF PART	MATERIAL	NOTES

DWG.	JUN.LI	DATE	11.10.20	UNITS	MM	SHEET/OF	1/1
CHK.		DATE		SCALE	2:1 (:)		
APP.		DATE					

	REV.	CONTENT	CHK.	DATE		DINKLE ENTERPRISE CO.,LTD	NAME	DKB10-XXPC
	DWG NO.	SP-03-DKB10XXC						