



| Normal Geometric Tolerancing | | | |
|---|-------------------|-----------------------------|-------|
| | ⊖ | ⊕ | |
| 0 to 100 over 100 to 150 over 150 | 0.2 0.3 0.5 | 0 to 10 over 10 0.3 | |
| Total Pitch Tolerances | | Normal dimension Tolerances | |
| 0<U<=30 | ±0.20 | 0~30 | ±0.25 |
| 30<U<=53 | ±0.25 | over 30~53 | ±0.30 |
| 53<U<=70 | ±0.30 | over 53~70 | ±0.35 |
| 70<U<=90 | ±0.35 | over 70~90 | ±0.44 |

NOTES:

1. RoHS Compliance

| REV. | CONTENT | CHK. | DATE |
|------|---------|------|------|
| | | | |

| DWG. | LWF | DATE | 10.09.29 |
|------|-----|------|----------|
| CHK. | | DATE | |
| APP. | | DATE | |

| ITEM | NAME OF PART | MATERIAL | NOTES |
|------|--------------|----------|-----------------|
| 1 | END COVER | PA66 | UL94-V0 GRAY |

| DWG NO. | SP-03-PM25WSC0 |
|---------|------------------|
| NAME | PM2.5WSC |
| SCALE | 4:1 (:) |
| UNITS | MM SHEET/OFF 1/1 |