

VI TELEFILTER**Filter specification****TFS 160F****1/5****Measurement condition**

Ambient temperature:	25	°C
Input power level:	0	dBm
Terminating impedance: *		
Input:	82 Ω	-28 pF
Output:	82 Ω	-22 pF

Characteristics**Remark:**

The reference level for the relative attenuation a_{rel} of the TFS 160F is the minimum of the pass band attenuation a_{min} . The minimum of the pass band attenuation a_{min} is defined as the insertion loss a_e . The centre frequency f_c is the arithmetic mean value of the upper and lower frequencies at the 3 dB filter attenuation level relative to the insertion loss a_e . The nominal frequency f_N is fixed at MHz without any tolerance. The given values for both the relative attenuation a_{rel} and the group delay ripple have to be achieved at the frequencies given below even if the centre frequency f_c is shifted due to the temperature coefficient of frequency TC_f in the operating temperature range and due to a production tolerance for the centre frequency f_c .

D a t a		typ. value		tolerance / limit		
Insertion loss (reference level)	a_e	17,3	dB	max.	19,0	dB
Nominal frequency	f_N	-			160,0	MHz
Centre frequency	f_c^{**}	160,0	MHz	max.	± 150	kHz
Passband	PB	-		f_N	$\pm 4,375$	MHz
Pass band ripple (p-p)		0,5	dB	max.	1	dB
Bandwidth	BW					
1 dB		9,19	MHz	min.	8,8	MHz
3 dB		9,65	MHz	min.	9,4	MHz
40 dB		11,33	MHz	max.	11,75	MHz
Relative attenuation	a_{rel}					
f_c	$\pm 4,40$ MHz	$\pm 4,40$ MHz	0,5 dB	max.	1	dB
$f_c \pm 4,40$ MHz	$\pm 4,70$ MHz	$\pm 4,70$ MHz	2 dB	max.	3	dB
$f_c - 140,00$ MHz	$- 5,88$ MHz	$- 5,88$ MHz	43 dB	min.	40	dB
$f_c + 5,88$ MHz	$+ 200,00$ MHz	$+ 200,00$ MHz	48 dB	min.	40	dB
Group delay ripple within PB (p-p)		70	ns	max.	200	ns
Operating temperature range	OTR	-			- 25 °C ... + 80 °C	
Storage temperature range		-			- 40 °C ... + 85 °C	
Temperature coefficient of frequency	TC_f^{***}	-18	ppm/K		-	

*) The terminating impedances depend on parasitics and q-values of matching elements and the board used, and are to be understood as reference values only. Should there be additional questions do not hesitate to ask for an application note or contact our design team.



**) at ambient temperature

***) $\Delta f_c(\text{Hz}) = TC_f(\text{ppm/K}) \times (T - T_A) \times f_{CAT}(\text{MHz})$


Generated:**Checked / Approved:**

Tele Filter GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.


VI TELEFILTER**Filter specification****TFS 160F****2/5****Filter characteristic****Construction and pin connection**

(All dimensions in mm)



1	Ground
2	Ground
3	Ground
4	Ground
5	Output
6	Output RF Return
7	Ground
8	Ground
9	Ground
10	Ground
11	Input
12	Input RF Return

Date code: Year + week
 T 2005
 U 2006
 V 2007
 ...

50 Ohm Test circuit

Tele Filter GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

VI TELEFILTER**Filter specification****TFS 160F****3/5****Stability characteristics**

After the following tests the filter shall meet the whole specification:

1. Shock: 500g, 1 ms, half sine wave, 3 shocks each plane;
DIN IEC 68 T2 - 27
2. Vibration: 10 Hz to 500 Hz, 0,35 mm or 5 g respectively, 1 octave per min, 10 cycles per plan, 3 plans;
DIN IEC 68 T2 - 6
3. Change of temperature: -55 °C to 125°C / 30 min. each / 10 cycles
DIN IEC 68 part 2 – 14 Test N
4. Resistance to solder heat (reflow): reflow possible: twice max.;
for temperature conditions refer to the attached "Air reflow temperature conditions" on page 4;


Packing

Tape & Reel: IEC 286 – 3, with exeption of value for N and minimum bending radius;
tape type II, embossed carrier tape with top cover tape on the upper side;


max. pieces of filters peer reel:	1700
reel of empty components at start:	min. 300 mm
reel of empty components at start including leader:	min. 500 mm
trailer:	min. 300 mm

Tape (all dimensions in mm)

W : 24,00 +0,30/-0,10
 Po : 4,00 ± 0,1
 Do : 1,50 +0,1/-0
 E : 1,75 ± 0,10
 F : 11,50 ± 0,10
 G(min) : 0,60
 P2 : 2,00 ± 0,1
 P1 : 12,00 ± 0,1
 D1(min) : 1,50
 Ao : 7,10 ± 0,10
 Bo : 13,90 ± 0,10
 Ct : 21,5 ± 0,1

**Reel (all dimensions in mm)**

A : 330
 W1 : 24,4 +2/-0
 W2(max) : 30,4
 N(min) : 60
 C : 13,0 +0,5/-0,2




The minimum bending radius is 45 mm.

Tele Filter GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Air reflow temperature conditions

Conditions	Exposure
Average ramp-up rate (30°C to 217°C)	less than 3°C/second
> 100°C	between 300 and 600 seconds
> 150°C	between 240 and 500 seconds
> 217°C	between 30 and 150 seconds
Peak temperature	max. 260°C
Time within 5°C of actual peak temperature	between 10 and 30 seconds
Cool-down rate (Peak to 50°C)	less than 6°C/second
Time from 30°C to Peak temperature	no greater than 300 seconds

Chip-mount air reflow profile

VI TELEFILTER**Filter specification****TFS 160F****5/5****History**

Version	Reason of changes	Name	Date
1.0	- Generation of development specification	Strehl	24.05.2005
1.1	- terminating impedance, typical values and matching configuration added	Pfeiffer	20.10.2005

Tele Filter GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.