

VI TELEFILTER

Filter specification

TFS 215A

1/5

Measurement condition

Ambient temperature:	23	°C
Input power level:	0	dBm
Terminating impedance: *		
Input:	530 Ω -3,28 pF	
Output:	530 Ω -2,58 pF	
External Coil:	82 nH	

Characteristics

Remark:

The reference level for the relative attenuation a_{rel} of the TFS 215A is the minimum of the pass band attenuation a_{min} . The minimum of the pass band attenuation a_{min} is defined as the insertion loss a_e . The centre frequency f_c is the arithmetic mean value of the upper and lower frequencies at the 3 dB filter attenuation level relative to the insertion loss a_e . The nominal frequency f_N is fixed at 215 MHz without any tolerance. The given values for both the relative attenuation a_{rel} and the group delay ripple have to be achieved at the frequencies given below even if the centre frequency f_c is shifted due to the temperature coefficient of frequency TC_f in the operating temperature range and due to a production tolerance for the centre frequency f_c .

D a t a		typ. value		tolerance / limit		
Insertion loss (reference level)		a_e	3,4 dB	max.	5	dB
Nominal frequency		f_N			215,0	MHz
Centre frequency		f_c	215,015 MHz		-	
Passband		PB		f_N	± 75,0	kHz
Pass band ripple			0,4 dB	max.	2	dB
Bandwidth		BW				
2	dB		280 kHz	min.	150	kHz
Relative attenuation		a_{rel}				
f_N	...	$f_N \pm 100$ kHz	0,5 dB	max.	3	dB
$f_N \pm 400$ kHz	...	$f_N \pm 600$ kHz	45 dB	min.	25	dB
$f_N \pm 600$ kHz	...	$f_N \pm 800$ kHz	45 dB	min.	35	dB
$f_N \pm 800$ kHz	...	$f_N \pm 1,6$ MHz	51 dB	min.	40	dB
$f_N \pm 1,6$ MHz	...	$f_N \pm 3,0$ MHz	52 dB	min.	45	dB
$f_N \pm 3,0$ MHz	...	$f_N \pm 30,0$ MHz	55 dB	min.	53	dB
Group delay ripple within PB			0,7 µs	max.	1,2	µs
Operating temperature range		OTR	-	- 30 °C ... + 85 °C		
Storage temperature range			-	- 40 °C ... + 85 °C		
Frequency inversion temperature			+25 °C	-		
Temperature coefficient of frequency		TC_f **	-0,04 ppm/K ²	-		

*) The terminating impedances depend on parasitics and q-values of matching elements and the board used, and are to be understood as reference values only. Should there be additional questions do not hesitate to ask for an application note or contact our design team.



**) $\Delta f(\text{Hz}) = TC_f(\text{ppm/K}^2) \times (T - T_0)^2 \times f_{T0}(\text{MHz})$

Generated:


Checked / Approved:

Tele Filter GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.


VI TELEFILTER**Filter specification****TFS 215A****2/5****Filter characteristic****Construction and pin connection**

(All dimensions in mm)



1	Output
2	Output
3	External Coil
4	Ground
5	Ground
6	Input
7	Input RF Return
8	Ground
9	Ground
10	Ground

Date code: Year + week
 T 2005
 U 2006
 V 2007
 ...

50 Ω test circuit

Tele Filter GmbH
 Potsdamer Straße 18
 D 14 513 TELTOW / Germany
 Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
 E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Stability characteristics

After the following tests the filter shall meet the whole specification:

1. Shock: 500g, 1 ms, half sine wave, 3 shocks each plane;
DIN IEC 68 T2 - 27
2. Vibration: 10 Hz to 500 Hz, 0,35 mm or 5 g respectively, 1 octave per min, 10 cycles per plan, 3 plans;
DIN IEC 68 T2 - 6
3. Change of temperature: -55 °C to 125°C / 30 min. each / 10 cycles
DIN IEC 68 part 2 – 14 Test N
4. Resistance to solder heat (reflow): reflow possible: twice max.;
for temperature conditions refer to the attached "Air reflow temperature conditions" on page 4;


Packing

Tape & Reel: IEC 286 – 3, with exeption of value for N and minimum bending radius;
tape type II, embossed carrier tape with top cover tape on the upper side;


max. pieces of filters peer reel:	2000
reel of empty components at start:	min. 300 mm
reel of empty components at start including leader:	min. 500 mm
trailer:	min. 300 mm

Tape (all dimensions in mm)

W : 16,00 ± 0,3
 Po : 4,00 ± 0,1
 Do : 1,50 +0,1/-0
 E : 1,75 ± 0,10
 F : 7,50 ± 0,10
 G(min) : 0,60
 P2 : 2,00 ± 0,1
 P1 : 12,00 ± 0,1
 D1(min) : 1,50
 Ao : 7,60 ± 0,10
 Bo : 9,60 ± 0,10
 Ct : 13,5

**Reel (all dimensions in mm)**

A : 330
 W1 : 16,4
 W2(max) : 22,4
 N(min) : 50
 C : 13,0




The minimum bending radius is 45 mm.

Tele Filter GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Air reflow temperature conditions

Conditions	Exposure
Average ramp-up rate (30°C to 217°C)	less than 3°C/second
> 100°C	between 300 and 600 seconds
> 150°C	between 240 and 500 seconds
> 217°C	between 30 and 150 seconds
Peak temperature	max. 260°C
Time within 5°C of actual peak temperature	between 10 and 30 seconds
Cool-down rate (Peak to 50°C)	less than 6°C/second
Time from 30°C to Peak temperature	no greater than 300 seconds

Chip-mount air reflow profile

VI TELEFILTER**Filter specification****TFS 215A****5/5****History**

Version	Reason of Changes	Name	Date
1.0	Generation of development specification	Strehl	11.04.2005
1.1	Generation of filter specification	Strehl	13.05.2005
1.2	Correct magnitude of relative attenuation	Strehl	20.05.2005
1.3	Changed typical value for parabolic temperature coefficient	Strehl	26.02.2007

Tele Filter GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.