

VI TELEFILTER**Filter specification****TFS 270 C****1/4****Measurement condition**

Ambient temperature: 23 °C
 Input power level: 0 dBm
 Terminating impedance input: 440 Ω || -1,40 pF
 Terminating impedance output : 440 Ω || -1,40 pF
 ext. coil pin 4: 120 nH

Construction

see page 2

Characteristics

Remark:

Reference level for the relative attenuation a_{rel} of the TFS 270C is the minimum of the pass band attenuation a_{min} . The minimum of the pass band attenuation a_{min} is defined as the insertion loss a_e . The nominal frequency f_N is fixed on 270,000 MHz without tolerance. The values of the pass band ripple and the relative attenuation a_{rel} are guaranteed in the whole operating temperature range. The frequency shift of the filter in the operating temperature range is included in the measurement tolerance scheme.




Preliminary Data		typ. value		tolerance / limit	
Insertion loss (Reference level)	$a_e = a_{min}$	3	dB	max 5	dB
Nominal frequency	f_N	-		270,000	MHz
Pass band ripple $f_N - 70$ kHz ... $f_N + 70$ kHz $f_N - 90$ kHz ... $f_N + 90$ kHz		0,5 1,0		max 2 max 3	dB dB
Relative attenuation	a_{rel}				
270,0 MHz $\pm$ 400 kHz ... 270,0 MHz $\pm$ 600 kHz		30	dB	min 20	dB
270,0 MHz $\pm$ 600 kHz ... 270,0 MHz $\pm$ 30 MHz		50	dB	min 40	dB
Group delay distortion	GDD				
270,0 MHz $\pm$ 70 kHz		0,5	μ s	max 2	μ s
Operating temperature range		- 20 °C ... + 85 °C			
Storage temperature range		- 30 °C ... + 85 °C			
Temperature coefficient of frequency	TC_f	- 0,036	ppm/K ²	-	
Frequency inversion temperature		+ 25	°C	-	

Generated:**Checked / approved:**
Construction and pin configuration
 (All dimensions in mm)

VI TELEFILTER
 Potsdamer Straße 18
 D 14 513 TELTOW / Germany
 Tel: (+49) 3328 4784-52 / Fax: (+49) 3328 4784-30
 E-Mail: tft@telefilter.com

Vectron International, Inc.
 267 Lowell Road
 Hudson, NH 03051 / USA
 Tel: (603) 598-0070 Fax: (603) 598-0075
 E-Mail: vti@vtinh.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

VI TELEFILTER**Filter specification****TFS 270 C****2/4****50 Ohm Test circuit 1****50 Ohm Test circuit 2****VI TELEFILTER**

Potsdamer Straße 18
D 14 513 TELTOW / Germany

Tel: (+49) 3328 4784-52 / Fax: (+49) 3328 4784-30

E-Mail: tft@telefilter.com

Vectron International, Inc.

267 Lowell Road
Hudson, NH 03051 / USA

Tel: (603) 598-0070 Fax: (603) 598-0075

E-Mail: vti@vtinh.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

VI TELEFILTER**Filter specification****TFS 270 C****3/4****Stability Characteristics**

After the following tests the filter shall meet the whole specification:


1. Shock: 100g, 18 ms, half sine wave, 3 shocks each plane;
DIN IEC 68 T2 - 27
2. Vibration: 10 Hz to 500 Hz, 0,075 mm or 1g respectively, 1 octave per min, 10 cycles per plan, 3 plans;
DIN IEC 68 T2 - 6
3. Damp heat: 90 % to 95 % rel. humidity, 40 °C, 10 days;
(steady state) DIN IEC 68 - 2 - 3
4. Resistance to solder heat (reflow): max. 2 times reflow process;
for temperature conditions refer to the attached "Air reflow temperature conditions" on sheet 4;

Packing


Tape & Reel: IEC 286 - 3, with exception of value for N and minimum bending radius;
tape type II, embossed carrier tape with top cover tape on the upper side;
max. pieces of filters per reel: 3400

Tape (all dimensions in mm)

W	:	16	± 0,3
Po	:	4	± 0,1
Do	:	1,5	+ 0,5
D1	:	1,5	+ 0,5
E	:	1,75	± 0,1
F	:	7,5	± 0,1
G (min)	:	0,75	
P2	:	2	± 0,05
P1	:	8	± 0,1
D1(min)	:	1,5	
Ao	:	5,4	± 0,1
Bo	:	5,4	± 0,1

**Reel (all dimensions in mm):**

A	:	330
W1	:	16,4 +2
W2 (max)	:	22,4
N (min)	:	>= 90
C	:	13 ± 0,25



The minimum bending radius is 45 mm. The mounting surface of the filters faces the bottom side of the embossed carrier tape. The marking of the filters is able to read if the view is directed on the upper side of the carrier tape with the sprocket holes on the right side of the tape.

VI TELEFILTER

Potsdamer Straße 18
D 14 513 TELTOW / Germany

Tel: (+49) 3328 4784-52 / Fax: (+49) 3328 4784-30

E-Mail: tft@telefilter.com

Vectron International, Inc.

267 Lowell Road
Hudson, NH 03051 / USA

Tel: (603) 598-0070 Fax: (603) 598-0075

E-Mail: vti@vtinh.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Air reflow temperature conditions

1st and 2nd air reflow profile

Name:	pre-heating periods	main-heating periods	peak temperature
Temperature:	150 °C - 170 °C	over 200 °C	255 °C ± 5 °C
Time:	60 sec. - 90 sec.	20 sec. - 25 sec.	

Chip-mount air reflow profile




Table for temperature vs. time during the air reflow process

Tolerance of temperatures: ± 5 °C

time / sec.	temperature / °C	time / sec.	temperature / °C
0	23	140	160
10	34	150	161
20	46	160	164
30	60	170	170
40	80	180	180
50	103	190	205
60	121	195	230
70	134	200	255
80	143	205	230
90	150	210	205
100	154	215	180
110	156	220	165
120	158	230	140
130	159	240	120