

**VI TELEFILTER****Filter specification****TFS 300 C****1/5****1. Measurement condition :**

Ambient temperature $T_A$ :	25 °C	
Input power level:	0 dBm	
Terminating impedances at $f_C$ *):	for input: 176 $\Omega$   - 6,19 pF.	
	for output: 775 $\Omega$   - 3,52 pF.	

**2. Characteristics**

Remark: Reference level for the relative attenuation  $a_{rel}$  of the **TFS 300C** is the minimum of the pass band attenuation  $a_{min}$ . The minimum of the pass band attenuation  $a_{min}$  is defined as the insertion loss  $a_e$ . The centre frequency  $f_C$  is the arithmetic mean value of the upper and lower frequencies at the 3 dB filter attenuation level relative to the insertion loss  $a_e$ . The nominal frequency  $f_N$  is fixed on **300 MHz** without tolerance. The given values for the relative attenuation  $a_{rel}$  and for the group delay ripple have to be reached at the frequencies given below also if the centre frequency  $f_C$  is shifted due to the temperature coefficient of frequency  $TC_f$  in the operating temperature range and due to a production tolerance for the centre frequency  $f_C$ .

Data	typ. value	tolerance / limit
<b>Insertion loss (Reference level) <math>a_e</math></b>	17 dB	max. 20 dB
<b>Nominal frequency <math>f_N</math></b>	-	300 MHz
<b>Centre frequency <math>f_C</math> at ambient temperature (<math>f_{CTA}</math>)</b>	300,02 MHz	
<b>Pass band (PB) :</b>		$f_N - 2,05$ MHz ... $f_N + 2,05$ MHz
<b>Amplitude ripple in PB (p-p) :</b>	0,8 dB	max. 1 dB
<b>Bandwidth :</b>		
1 dB	4,55 MHz	min. 4,1 MHz
3 dB	5,25 MHz	min. 5,0 MHz
3 dB	5,25 MHz	max. 5,5 MHz
20 dB	6,96 MHz	
40 dB	9,30 MHz	max. 10 MHz
<b>Relative attenuation <math>a_{rel}</math></b>		
$f_N \pm 2,05$ MHz	-	max. 1 dB
$f_N \pm 2,5$ MHz	-	max. 3 dB
$f_N \pm 2,75$ MHz	-	min. 3 dB
$f_N \pm 5$ MHz	43...45 dB	min. 40 dB
$f_N - 25$ MHz	49...54 dB	min. 45 dB
$f_N + 7$ MHz	49...54 dB	min. 43 dB
$f_N \pm 25$ MHz	55...70 dB	min. 50 dB
$f_N - 290$ MHz	90 dB	
$f_N + 100$ MHz	90 dB	
<b>Group delay ( mean value in PB ):</b>	1,1 $\mu$ s	max. 1,5 $\mu$ s
<b>Group delay ripple (p-p) in :</b> $f_N \dots f_N \pm 2,2$ MHz	60 ns	max. 100 ns
<b>Deviation from linear phase (p-p)</b> $f_N \dots f_N \pm 1,8$ (2,5) MHz	2° (2,6°)	
<b>Triple transit attenuation compared to main signal</b>	39 dB	
<b>Crosstalk</b>	60...65 dB	
<b>Substrate material</b>	Quartz	
<b>Frequency inversion temperature (<math>T_o</math>)</b>	30 °C	
<b>Temperature coefficient of frequency (<math>TC_f</math>)</b>	-0,030 ppm/K <sup>2</sup>	
<b>Frequency deviation of <math>f_C</math> over temperature: **)</b>	$\Delta f_C(\text{Hz}) = TC_f(\text{ppm/K}) \times (T - T_o)^2 \times f_{r0}(\text{MHz})$	
<b>Operating temperature range</b>		- 20 °C ... + 70 °C
<b>Storage temperature range</b>		- 40 °C ... + 85 °C

\*) The terminating impedances depend on parasitics and q-values of matching elements and the board used, and are to be understood as reference values only. Should there be additional questions do not hesitate to ask for an application note or contact our design team.


\*\*)  $f_0 = f_{r0}$  is reference frequency  $f_C$  at frequency inversion temperature ( $T_o$ )

**Generated:** Dunzow W.



**Checked / approved:** Dr. Bert Wall

**VI TELEFILTER****Potsdamer Straße 18****D 14 513 TELTOW / Germany****Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30****E-Mail: [tft@telefilter.com](mailto:tft@telefilter.com)**

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

**3. Package, pin grid 2,54 mm**

**Pin 9 - Input.**  
Pin 10 - Input RF Return.  
**Pin 4 - Output.**  
Pin 5 - Output RF Return.  
Pin 1-3, 6-8 - Package Ground.

**4. 50  $\Omega$  matching network ( please refer to the application note for further details ) :**

For final test we use scheme 2.

**VI TELEFILTER**

Potsdamer Straße 18

D 14 513 TELTOW / Germany

Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30

E-Mail: [tft@telefilter.com](mailto:tft@telefilter.com)

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

**5. Stability characteristics :**

After the following tests the filter shall meet the whole specification:

1. Shock: 500g, 18 ms, half sine wave, 3 shocks each plane;  
DIN IEC 68 T2 - 27
2. Vibration: 10 Hz to 500 Hz, 0,35 mm or 5g respectively, 1 octave per min, 10 cycles per plan, 3 plans;  
DIN IEC 68 T2 - 6
3. Change of temperature: -55 °C to 125°C / 30 min. each / 10 cycles  
DIN IEC 68 part 2 – 14 Test N
4. Resistance to solder heat (reflow): reflow possible: twice max. ;  
for temperature conditions, please refer to the attached "Air reflow temperature conditions" on page 4;


**6. Packing**

Tape & Reel: DIN IEC 286 - 3, with exception of value for N and minimum bending radius;  
tape type II, embossed carrier tape with top cover tape on the upper side;


max. pieces of filters per reel: 1700  
reel of empty components at start: min 300 mm  
reel of empty components at start including leader: min 500 mm  
Trailer: min 300 mm

**Tape (all dimensions in mm)**

W	: 24± 0,3
Po	: 4 ± 0,1
Do	: 1,5 + 0,1
E	: 1,75 ± 0,1
F	: 7,5 ± 0,1
G (min)	: 0,6
P2	: 2 ± 0,1
P1	: 8 ± 0,1
D1(min)	: 1,5
Ao	: 5,6 ± 0,1
Bo	: 11,8 ± 0,
CT	: 21,5 ± 0,1

**Reel (all dimensions in mm):**

A	: 330
W1	: 24,4 + 2/-0
W2(max)	: 30,4
N(min)	: 60
C	: 13,0 +0,5 / -0,2



The minimum bending radius is 45 mm. The mounting surface of the filters faces the bottom side of the embossed carrier tape. Markings on the filters can be read if the upper side of the carrier tape is regarded with the sprocket holes on its right.

**VI TELEFILTER**

Potsdamer Straße 18

D 14 513 TELTOW / Germany

Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30

E-Mail: [tft@telefilter.com](mailto:tft@telefilter.com)

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

**7. Air reflow temperature conditions :**

1st and 2nd air reflow profile

Name:	pre-heating periods	main-heating periods	peak temperature
Temperature:	150 °C - 170 °C	over 200 °C	255 °C ± 5 °C
Time:	60 sec. - 90 sec.	20 sec. - 25 sec.	


**Chip-mount air reflow profile**

Table for temperature vs. time during the air reflow process

Tolerance of temperatures: ± 5 °C

time / sec.	temperature / °C	time / sec.	temperature / °C
0	23	140	160
10	34	150	161
20	46	160	164
30	60	170	170
40	80	180	180
50	103	190	205
60	121	195	230
70	134	200	255
80	143	205	230
90	150	210	205
100	154	215	180
110	156	220	165
120	158	230	140
130	159	240	120

**VI TELEFILTER****Potsdamer Straße 18****D 14 513 TELTOW / Germany****Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30****E-Mail: [tft@telefilter.com](mailto:tft@telefilter.com)**

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

**VI TELEFILTER****Filter specification****TFS 300 C****5/5****History :**

<b>Version</b>	<b>Reason of Changes</b>	<b>Name</b>	<b>Date</b>
1.0	Generate preliminary specification according to customer requirements	Dunzow W.	18.06.2001
1.1	- change " Relative attenuation ( $a_{rel}$ ) " from $f_N \pm 7 \text{ MHz} \dots f_N \pm 25 \text{ MHz}$ min. 47 dB to $f_N - 25 \text{ MHz} \dots f_N - 7 \text{ MHz}$ min. 45 dB $f_N + 7 \text{ MHz} \dots f_N + 25 \text{ MHz}$ min. 43 dB - change termination impedance from : from for input: $215 \Omega$   - 6,1 pF. for output: $1190 \Omega$   - 3,3 pF. to for input: $176 \Omega$   - 6,19 pF. for output: $775 \Omega$   - 3,52 pF.	Dunzow W.	08.04.2002

**VI TELEFILTER****Potsdamer Straße 18****D 14 513 TELTOW / Germany****Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30****E-Mail: [tft@telefilter.com](mailto:tft@telefilter.com)**

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.