

VI TELEFILTER**Filter Specification****TFS 430B****1/5****Measurement condition**

Ambient temperature T_A : 23 °C
 Input power level: 0 dBm.
 Terminating Impedance at f_c^* :
 for input: 260 Ω || 6,7 pF
 for output: 290 Ω || 7,1 pF

Characteristics**Remark:**

Reference level for the relative attenuation a_{rel} of the TFS 430B is the minimum of the pass band attenuation a_{min} . The minimum of the pass band attenuation a_{min} is defined as the insertion loss a_e . The centre frequency f_c is the arithmetic mean value of the upper and lower frequencies at the 3 dB filter attenuation level relative to the insertion loss a_e . The nominal frequency f_N is fixed at 430 MHz without tolerance. The given values for the relative attenuation a_{rel} and for the group delay ripple have to be reached at the frequencies given below even if the centre frequency f_c is shifted due to the temperature coefficient of frequency TC_f in the operating temperature range and due to a production tolerance for the centre frequency f_c .

D a t a		typ. value		tolerance / limit		
Insertion loss (Reference level)	$a_e = a_{min}$	9,2	dB	max.	10	dB
Nominal frequency	f_N	-		430		MHz
Centre frequency	f_c	430	MHz	-		
Relative attenuation	a_{rel}					
f_N	$\dots f_N \pm 2$ MHz	-		max.	1	dB
$f_N \pm 2$	$\dots f_N \pm 3,325$ MHz	-		max.	1,5	dB
$f_N \pm 9$	$\dots f_N \pm 50$ MHz	37	dB	min.	30	dB
$f_N \pm 50$	$\dots f_N \pm 100$ MHz	45	dB	min.	40	dB
Phase Linearity	$f_N \pm 2$ MHz	0,7	°rms	max.	3	°rms
Operating temperature range		-		- 30 °C ... + 70 °C		
Storage temperature range		-		- 35 °C ... + 85 °C		
Temperature coefficient of frequency TC		- 19	ppm/K	-		
Frequency inversion temperature		+ 25	°C	-		

*) The terminating impedances depend on parasitics and q-values of matching elements and the board used, and are to be understood as reference values only. Should there be additional questions, do not hesitate to ask for an application note or contact our design team.

generated: _____


checked / approved: _____

TELEFILTER GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.


Construction, pin configuration and 50 Ω - matching network

(All dimensions in mm)



Pin 1	output	Pin 5	input
Pin 2	output	Pin 6	input
Pin 3	ground	Pin 7	ground
Pin 4	package ground	Pin 8	package ground

date code:	year + week
N	2001
P	2002
R	2003
...	

50 Ohm Test circuit, balanced driven

Stability Characteristics

After the following tests the filter shall meet the whole specification:


1. Shock: 500g, 18 ms, half sine wave, 3 shocks each plane;
DIN IEC 68 T2 - 27
2. Vibration: 10 Hz to 500 Hz, 0,35 mm or 5g respectively, 1 octave per min, 10 cycles per plan, 3 plans;
DIN IEC 68 T2 - 6
3. Change of temperature: -55 °C to 125°C / 30 min. each / 10 cycles
DIN IEC 68 part 2 – 14 Test N
4. Resistance to solder heat (reflow): reflow possible: twice max.;
for temperature conditions, please refer to the attached "Air reflow temperature conditions" on page 4;

Packing


Tape & Reel: IEC 286 - 3, with exception of value for N and minimum bending radius;
tape type II, embossed carrier tape with top cover tape on the upper side;
max. pieces of filters per reel: 3000
reel of empty components at start: min 300 mm
reel of empty components at start including leader: min 500 mm
trailer min 300 mm

Tape (all dimensions in mm)

W	: 12 ± 0,3
Po	: 4 ± 0,1
Do	: 1,5 + 0,5
D1	: 1,5 + 0,5
E	: 1,75 ± 0,1
F	: 7,5 ± 0,1
G (min)	: 0,75
P2	: 2 ± 0,05
P1	: 8 ± 0,1
D1 (min)	: 1,5
Ao	: 5,3 ± 0,1
Bo	: 5,3 ± 0,1

**Reel (all dimensions in mm):**

A	: 330
W1	: 12,4 + 0,2
W2 (max)	: 18,4
N (min)	: 50
C	: 13 + 0,2 / -0,5



The minimum bending radius is 45 mm. The mounting surface of the filters faces the bottom side of the embossed carrier tape. Markings on the filters can be read if the upper side of the carrier tape is regarded with the sprocket holes on its right.

TELEFILTER GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Air reflow temperature conditions

1st and 2nd air reflow profile

Name:	pre-heating periods	main-heating periods	peak temperature
Temperature:	150 °C - 170 °C	over 200 °C	255 °C ± 5 °C
Time:	60 sec. - 90 sec.	20 sec. - 25 sec.	


Chip-mount air reflow profile

Table for temperature vs. time during the air reflow process

Tolerance of temperatures: ± 5 °C

time / sec.	temperature / °C	time / sec.	temperature / °C
0	23	140	160
10	34	150	161
20	46	160	164
30	60	170	170
40	80	180	180
50	103	190	205
60	121	195	230
70	134	200	255
80	143	205	230
90	150	210	205
100	154	215	180
110	156	220	165
120	158	230	140
130	159	240	120

VI TELEFILTER**Filter Specification****TFS 430B****5/5****History**

Version	Reason of Changes	Name	Date
1.0	- generation of specification	Pfeiffer	30.07.2002
1.1	- drawing matching networks	Dunzow	27.08.2002
1.2	- adding typical values and terminating impedances	Pfeiffer	26.11.2002
2.0	- changing terminating impedances	Pfeiffer	29.04.2003

TELEFILTER GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.