

VI TELEFILTER

Filter specification

TFS 456L

1/5

Measurement condition

Ambient temperature:	23	°C
Input power level:	0	dBm
Terminating impedance: *		
Input:	550 Ω -2,5 pF	
Output:	650 Ω -2,3 pF	

Characteristics

Remark:

The reference level for the relative attenuation a_{rel} of the TFS 456L is the minimum attenuation in the pass band. The maximum attenuation in the pass band is defined as the insertion loss a_e . The nominal frequency f_N is fixed at 456,0 MHz without any tolerance or limit. The values of relative attenuation a_{rel} are guaranteed for the whole operating temperature range. The frequency shift of the filter in the operating temperature range is included in the production tolerance scheme.

D a t a		typ. value		tolerance / limit		
Insertion loss (reference level)		$a_e = a_{min}$	9,2	dB	max.	11,0
			-			-
Nominal frequency		f_N	-		456,0	MHz
Passband			-		$f_N \pm 1,6$	MHz
Relative attenuation		a_{rel}				
$f_N - 1,6$	MHz	$f_N + 1,6$	MHz	0,3	dB	max. 1
$f_N - 1,75$	MHz	$f_N + 1,75$	MHz	1	dB	max. 3
$f_N - 455$	MHz	$f_N - 200$	MHz	80	dB	min. 30
$f_N - 200$	MHz	$f_N - 96$	MHz	70	dB	min. 40
$f_N - 96$	MHz	$f_N - 36$	MHz	60	dB	min. 50
$f_N - 36$	MHz	$f_N - 3,35$	MHz	47	dB	min. 40
$f_N + 3,35$	MHz	$f_N + 4$	MHz	45	dB	min. 35
$f_N + 4$	MHz	$f_N + 200$	MHz	45	dB	min. 40
$f_N + 200$	MHz	$f_N + 490$	MHz	60	dB	min. 30
Absolute Group Delay		at f_N	0,6	µs	max.	3
Group delay ripple			95	ns	max.	220
Return loss within PB			13	dB	min.	10
Input power level			-		max.	13
Operating temperature range		OTR	-		- 40 °C ... + 85°C	
Storage temperature range			-		- 45 °C ... + 85°C	
Frequency inversion temperature			20	°C		
Temperature coefficient of frequency		TC_f **	-0,04	ppm/K ²		

*) The terminating impedances depend on parasitics and q-values of matching elements and the board used, and are to be understood as reference values only. Should there be additional questions do not hesitate to ask for an application note or contact our design team.



**) $\Delta f(\text{Hz}) = TC_f(\text{ppm/K}^2) \times (T - T_0)^2 \times f_{cat}(\text{MHz})$.

Generated:


Checked / Approved:

Tele Filter GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.


VI TELEFILTER**Filter specification****TFS 456L****2/5****Filter characteristic****Construction and pin connection**

(All dimensions in mm)



1	Ground
2	Ground
3	Ground
4	Output
5	Output
6	Ground
7	Ground
8	Ground
9	Input
10	Input

Date code: Year + week
 T 2005
 U 2006
 V 2007
 ...

200 Ω Test circuit

Tele Filter GmbH
 Potsdamer Straße 18
 D 14 513 TELTOW / Germany
 Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
 E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

VI TELEFILTER**Filter specification****TFS 456L****3/5****Stability characteristics**

After the following tests the filter shall meet the whole specification:

1. Shock: 500g, 18 ms, half sine wave, 3 shocks each plane;
DIN IEC 68 T2 - 27
2. Vibration: 10 Hz to 500 Hz, 0,35 mm or 5 g respectively, 1 octave per min, 10 cycles per plan, 3 plans;
DIN IEC 68 T2 - 6
3. Change of temperature: -55 °C to 125°C / 30 min. each / 10 cycles
DIN IEC 68 part 2 – 14 Test N
4. Resistance to solder heat (reflow): reflow possible: twice max.;
for temperature conditions refer to the attached "Air reflow temperature conditions" on page 4;


Packing

Tape & Reel: IEC 286 – 3, with exeption of value for N and minimum bending radius;
tape type II, embossed carrier tape with top cover tape on the upper side;


max. pieces of filters peer reel:	3000
reel of empty components at start:	min. 300 mm
reel of empty components at start including leader:	min. 500 mm
trailer:	min. 300 mm

Tape (all dimensions in mm)

W	: 16,00 ± 0,3
Po	: 4,00 ± 0,1
Do	: 1,50 +0,1/-0
E	: 1,75 ± 0,1
F	: 7,50 ± 0,1
G(min)	: 0,60
P2	: 2,00 ± 0,1
P1	: 8,00 ± 0,1
D1(min)	: 1,50
Ao	: 5,50 ± 0,1
Bo	: 7,50 ± 0,1
Ct	: 13,5 ± 0,1

**Reel (all dimensions in mm)**

A	: 330
W1	: 16,4 +2/-0
W2(max)	: 22,4
N(min)	: 50
C	: 13,0 +0,5/-0,2




The minimum bending radius is 45 mm.

Tele Filter GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Air reflow temperature conditions

Conditions	Exposure
Average ramp-up rate (30°C to 217°C)	less than 3°C/second
> 100°C	between 300 and 600 seconds
> 150°C	between 240 and 500 seconds
> 217°C	between 30 and 150 seconds
Peak temperature	max. 260°C
Time within 5°C of actual peak temperature	between 10 and 30 seconds
Cool-down rate (Peak to 50°C)	less than 6°C/second
Time from 30°C to Peak temperature	no greater than 300 seconds

Chip-mount air reflow profile

VI TELEFILTER**Filter specification****TFS 456L****5/5**

Version	Reason of Changes	Name	Date
1.0	- Generation of development specification	Steiner	21.10.2004
1.1	- terminating impedance (preliminary values), typical values and filter characteristic added - air reflow temperature conditions modified	Pfeiffer	15.11.2004
1.2	- insertion loss typical value corrected to 8,9 dB	Pfeiffer	19.11.2004
1.3	- terminating impedance corrected - typical values and filter characteristic changed - reference level for the relative attenuation: minimum attenuation in the pass band	Pfeiffer	02.02.2005