

VI TELEFILTER**Filter specification****TFS 70H43****1/5****1. Measurement condition :**

Ambient temperature T_A : 23 °C.
 Input power level: 0 dBm.
 Terminating impedances in f_C *) : for input: 454 Ω | - 9,26 pF typical value.
 for output: 386 Ω | - 10,30 pF typical value.

2. Characteristics :

Remark:

Reference level for the relative attenuation a_{rel} of the **TFS 70H43** is the minimum of the pass band attenuation a_{min} . The minimum of the pass band attenuation a_{min} is defined as the insertion loss a_e . The reference frequency f_C is the arithmetic mean value of the upper and lower frequencies at the 3 dB filter attenuation level relative to the insertion loss a_e . The temperature coefficient of frequency T_{Cf} is valid both for the reference frequency f_C and the frequency response of the filter in the operating temperature range. The frequency shift of the filter in the operating temperature range is not included in the production tolerance scheme.

Data	typ. value	tolerance / limit		
Insertion loss (Reference level) a_e	22,5 dB	max.	25	dB
Centre frequency f_C at ambient temperature (f_{CTA})	70,0 MHz	70,00 $\pm$ 0,10 MHz		
Pass band (PB) :		$f_C \dots f_C \pm 13$ MHz		
Amplitude ripple in : $f_C - 12,25$ MHz ... $f_C + 12,25$ MHz	0,7 dB	max.	1	dB
Bandwidth (BW) : at ambient temperature T_A				
1 dB	24,80 MHz	min.	24,5	MHz
3 dB	26,30 MHz	min.	26	MHz
20 dB	29,98 MHz			
45 dB	31,8 MHz	max.	34	MHz
50 dB	32,0 MHz			
Relative attenuation a_{rel}				
$f_C \dots f_C \pm 12,25$ MHz	-	max.	1	dB
$f_C \pm 12,25$ MHz ... $f_C \pm 13$ MHz	-	max.	3	dB
$f_C \pm 17$ MHz ... $f_C \pm 25$ MHz	55 dB	min.	45	dB
$f_C \pm 25$ MHz ... $f_C \pm 50$ MHz	55...65 dB	min.	50	dB
Group delay (mean value in PB) :	1,05 μ s			
Group delay ripple in PB (p-p):	33 ns	max.	40	ns
Deviation from linear phase in PB (p-p) :	5 ° (r.m.s. 0,9 °)	max.	6°	
Triple transit attenuation compared to main signal	52 dB			
Crosstalk	60 dB			
Temperature coefficient of frequency (T_{Cf}) :	- 75 ppm/K			
Frequency deviation of f_C over temperature :	$\Delta f_C(\text{Hz}) = T_{Cf}(\text{ppm/K}) \times (T - T_A) \times f_{CTA} (\text{MHz})$			
Operating temperature range	- 25 °C ... + 80 °C			
Storage temperature range	- 40 °C ... + 85 °C			

*) The terminating impedances depend on parasitics and q-values of matching elements and the board used, and are to be understood as reference values only. Should there be additional questions do not hesitate to ask for an application note or contact our design team.

Generated: W. Dunzow



Checked / approved: Dr. Bert Wall

VI TELEFILTER**Potsdamer Straße 18****D 14 513 TELTOW / Germany****Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30****E-Mail: tft@telefilter.com**

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

3. Construction and pin connection

(all dimensions in mm)

**4. 50 Ω matching network (please refer to the application note for further details) :****VI TELEFILTER****Potsdamer Straße 18****D 14 513 TELTOW / Germany****Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30****E-Mail: tft@telefilter.com**

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

5. Stability characteristics :

After the following tests the filter shall meet the whole specification:

1. Shock: 500g, 18 ms, half sine wave, 3 shocks each plane;
DIN IEC 68 T2 - 27
2. Vibration: 10 Hz to 500 Hz, 0,35 mm or 5g respectively, 1 octave per min, 10 cycles per plan, 3 plans;
DIN IEC 68 T2 - 6
3. Change of temperature: -55 °C to 125°C / 30 min. each / 10 cycles
DIN IEC 68 part 2 – 14 Test N
4. Resistance to solder heat (reflow): reflow possible: twice max.;
for temperature conditions, please refer to the attached "Air reflow temperature conditions" on page 4;

6. Air reflow temperature conditions :

1st and 2nd air reflow profile

Name:	pre-heating periods	main-heating periods	peak temperature
Temperature:	150 °C - 170 °C	over 200 °C	255 °C ± 5 °C
Time:	60 sec. - 90 sec.	20 sec. - 25 sec.	


Air reflow profile

Table for temperature vs. time during the air reflow process

Tolerance of temperatures: ± 5 °C

time / sec.	temperature / °C	time / sec.	temperature / °C
0	23	140	160
10	34	150	161
20	46	160	164
30	60	170	170
40	80	180	180
50	103	190	205
60	121	195	230
70	134	200	255
80	143	205	230
90	150	210	205
100	154	215	180
110	156	220	165
120	158	230	140
130	159	240	120

VI TELEFILTER**Potsdamer Straße 18****D 14 513 TELTOW / Germany****Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30****E-Mail: tft@telefilter.com**

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

VI TELEFILTER**Filter specification****TFS 70H43****5/5****7. History :**

Version	Reason of changes	Name	Date
1.0	Generate filter specification.	Dunzow W.	18.07.2002

VI TELEFILTER**Potsdamer Straße 18****D 14 513 TELTOW / Germany****Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30****E-Mail: tft@telefilter.com**

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.