



TYPE	DIM A	DIM B	DIM H1	DIM H2	LENGTH PIN
1	3.00	4.70	6.50	4.38	12.90
2	3.00	4.83	6.50	3.50	12.10
3	7.00	4.70	6.50	3.50	16.00
4					
5					
6					
7					
8					
9					
10					
11					
12					
13					
14					



RECOMMEND PCB LAYOUT(TOLERANCE=±0.05)

- ## 1. MATERIAL

- 1.1 INSULATOR:THERMOPLASTIC(UL94 V-0).
1.2 CONTACT MATERIAL:COPPER ALLOY.

- ## 2. SPECIFICATION

- 2.1 CURRENT RATING:1.5 Amp.
2.2 INSULATION RESISTANCE:1000MΩ Min.
2.3 DIELECTRIC WITHSTANDING:600VAC.
2.4 CONTACT RESISTANCE:50mΩ Max.
2.5 OPERATING TEMPERATURE:−40°C TO+105°C.

3. PART NUMBER: DS1029-03

4. PRODUCT NUMBER CODE:

DS1029-03 - X X X X X X X X X - X

— PLATING LEVEL

B: LEVEL B

— PACKING TYPE

T: TRAY

R: TAPE ON REEL

B: TUBE

— PICK UP SUPPORT

S: W/

X: W/O

— BEND TYPE

1: R1 TYPE

—DIM.A B H1 H2 YPE
3. TYPE 3

3: TYPE 3

—MOUNTING TYPE

S: SMT TYPE

— HOUSING COLOR

B:BLACK

— CONNECTOR PLATING
8: FULL GOLD FLASH

8: FULL

— CONNECT TYPE
P-PLUG

NO. 25. 2

— No. OF CONTACTS
1*8

10

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	JLZ 03/012/15'		

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE		2.54mm PITCH PIN HEADER SINGLE ROW S.M.T TYPE	
X.	±0.60	X.	±5°	UNITS	mm				
.X	±0.38	.X	±3°	SHEET SIZE	A4	SERIES	DS1029-03 SERIES		
.XX	±0.25	.XX	±2°	 晨翔电子有限公司 CONNFLY CONNFLY ELECTRONIC CO. LTD					
DRAWING TYPE		CUSTOMER							
SCALE	1:1	SHEET	1 OF 1						
DRAWING NO.	C-DS1029-03-XXXXXXX								



晨翔电子有限公司

CONNFLY CONNFLY ELECTRONIC CO. LTD