



△△ SPECIFICATION
 Current Rating:16 Amp/Way Max.
 Voltage Rating:300V AC
 Contact Resistance:20 Milliohms Max.
 Withstanding Voltage:2500V AC(1 Minute)
 Test Time=60 Sec./1 PCS
 Operation Temperature:-40°C~+105°C
 Soldering Reliability:Test Temperature=250°C±10°C/
 5 Seconds Max.
 Wire Range:12~26 AWG
 Torque:5.0 Kgf.cm/M3
 Insulator Body(Housing):Polyamide(UL94V-0)
 Contact(Metal Housing):Copper Alloy,Nickel Plated
 Wire Guard:Copper Alloy,Tin Plated
 Screw:Steel,Galvanized With Cr3+ Plated
 RoHS Compliant

△△ TB 51 XX SW - XX - H
 (1) (2) (3) (4) (5) (6)

(1) TB:Terminal Block Pluggable Rising Clamp Type
 (2) 51:Pitch 5.08mm
 (3) XX:No. Of Position
 (4) SW:Female Screw Type
 (5) XX:Insulator Color
 Blank:Green
 BL:Blue
 BK:Black
 OR:Orange
 GE:Gray
 (6) H:RoHS Compliant

CATEGORY		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.50 .X ±0.30 .XX ±0.20 ANG. ±1°	△ A4	Modify P/N Code	HZF	08/07/2014	
PART No. TB51XXSW-XX-H		CHECKED BY			△ A3	Modify Spec.	HZF	02/12/2014	
DRAWING No. TB51XXSW-XX-H		DRAWING BY			△ A2	Modify P/N:TB51XXSW-H --> TB51XXSW-XX-H	HZF	12/16/2011	
SCALE	NONE	REV.	A4		△ A1	Modify Data	HZF	06/29/2010	
				UNIT	mm	△ A0	NEW RELEASE	HZF	04/10/2009
				NO.REV.	REVISIONS		CHK	DATE	